PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: A61M 16/00	A1	(11) International Publication Number: (43) International Publication Date:	WO 00/61212 19 October 2000 (19.10.00)
(21) International Application Number: PCT/US (22) International Filing Date: 12 April 2000 ((30) Priority Data: 09/291,715 14 April 1999 (14.04.99) (71) Applicant: VITAL SIGNS, INC. [-/US]; 20 Camp Totowa, NJ 07512 (US). (72) Inventor: MONGEON, Douglas, R.; 11201 South Orange Park Acres, CA 92869 (US). (74) Agents: MAYER, Richard, L. et al.; Kenyon & Ken Broadway, New York, NY 10004 (US).	12.04.0 Us Roz	BG, BR, BY, CA, CH, CN, DZ, EE, ES, FI, GB, GD, GE IN, IS, JP, KE, KG, KP, KR, I LV, MA, MD, MG, MK, MN, RO, RU, SD, SE, SG, SI, SF, UA, UG, UZ, VN, YU, ZA, Z KE, LS, MW, SD, SL, SZ, T (AM, AZ, BY, KG, KZ, MD, I (AT, BE, CH, CY, DE, DK, LU, MC, NL, PT, SE), OAPI CM, GA, GN, GW, ML, MR, Published	CR, CU, CZ, DE, DK, DM, E, GH, GM, HR, HU, ID, IL, KZ, LC, LK, LR, LS, LT, LU, MW, MX, NO, NZ, PL, PT, C, SL, TJ, TM, TR, TT, TZ, CW, ARIPO patent (GH, GM, Z, UG, ZW), Eurasian patent (ES, FI, FR, GB, GR, IE, IT, patent (BF, BJ, CF, CG, CI, NE, SN, TD, TG).

(54) Title: ARTIFICIAL AIRWAY DEVICE AND METHOD OF ITS USE

(57) Abstract

This invention is an artificial airway device used to facilitate lung ventilation in an unconscious patient; and methods of using, and inserting an artificial airway device. The device includes a curved but flexible airway tube (200), and a mask portion (100). A mask opening portion (110) is shaped so as to fit closely adjacent, and closely over the patient's laryngeal opening. A seating tip (120) includes a series of thin, flexible fins or gills (122, 125) which project from a finger portion (120) extending from the mask opening portion. The fins or gills seat against the pharyngeal side of the cricoid, just above the esophagus. The seating tip provides a reference ensuring that the mask portion is properly in place, and adequately anchored. An inflatable cuff (800) acts to anchor the airway in place.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑÜ	Australia	GA	Gabon	LV	Latvia	SZ.	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE .	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Кутдугал	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RÜ	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka -	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

ARTIFICIAL AIRWAY DEVICE AND METHOD OF ITS USE

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to artificial airway devices used to facilitate lung ventilation in unconscious patients, and more specifically to devices designed for placement above the laryngeal opening of the patient in order to prevent airway obstruction and to permit either spontaneous or controlled ventilation.

10 <u>DESCRIPTION OF RELATED ART</u>

15

20

To maintain open the airway of an unconscious patient under general anesthesia, it is common practice to use an endotracheal tube, which is a flexible tube of rubber or plastic which is inserted down through the trachea. Prior art endotracheal tubes frequently include an inflatable cuff disposed symmetrically around a distal end of the tube, which distal end is inserted into the trachea. The inflatable cuff is used to seal and secure the endotracheal tube in place.

Typically, the endotracheal tube is introduced through mouth or nose and the larynx into the trachea or windpipe, and then the cuff is inflated through a small auxiliary tube in order to form a seal against

5

10

15

20

25

30

35

the wall of the trachea. Introduction of the endotracheal tube into a patient is a skilled operation normally requiring use of a laryngoscope to guide the tube through the larynx, past the vocal cords and into the trachea. Intubation using an endotracheal tube is difficult or even impossible in some patients.

Moreover, there is a significant risk of damage to soft tissues or to the larynx when using an endotracheal tube. Likewise, there is a risk of accidental, but highly undesirable, intubation of the esophagus or of the right or left main bronchus when using an endotracheal tube.

Alternatively, oro- or naso-pharyngeal airway devices may be used to maintain open the airway of a patient under general anesthesia. An oro- or nasopharyngeal airway is a flexible tube extending from the mouth (oro-pharyngeal airway) or nose (naso-pharyngeal airway) into the patient's pharynx but not into the patient's larynx. An oro- or naso-pharyngeal airway is normally used in conjunction with a face mask over the patient's mouth and/or nose, unlike an endotracheal tube, which normally is not used with a mask. preventing obstruction of the airway by the tongue, an oro- or naso-pharyngeal airway device cannot be used conveniently for controlled ventilation of the patient and does not prevent inhalation of extraneous matter (i.e., aspiration). For these and other reasons this type of device is less desirable in many applications.

Prior art artificial airways (see for example, U.S. Patent Nos. 4,509,514; 4,995,388; 5,241,956; 5,249,571; 5,282,464; 5,297,547; 5,305,743; 5,355,879; 5,584,290; 5,632,271 and 5,682,880 to Archibald I. J. Brain -- collectively, the "Brain patents") use a curved tube and a laryngeal mask portion at one end of the tube. The mask portion includes a flexible annular inflatable collar which

surrounds a hollow interior space of the mask portion. The mask portion is pre-formed with a roughly elliptical shape which is purported to be capable of conforming to, and fitting within, the space behind the larynx to form a seal around the circumference of the laryngeal inlet without penetrating into the interior of the larynx. The curved tube opens into the mask portion and provides an airway with the axis of the tube substantially aligned with the length of the elliptical formation of the mask portion.

In the Brain patents, the curved tube opens into a lumen of the mask through an aperture which is provided with flexible cross-bars to prevent the aperture from being obstructed by the epiglottis, while permitting passage of a second smaller tube, such as an endotracheal or endobronchial tube, a suction catheter, or an inspection tube such as a fiber-optic broncho- or laryngoscope.

20 SUMMARY OF THE INVENTION

5

10

15

25

30

35

The present invention is an artificial airway device which is designed to overcome certain shortcomings which have been discovered with the use, in practice, of artificial airways of the prior art. The present invention is also designed to be inexpensive, to be easy to insert without causing damage to the patient and without the need for a laryngoscope or other inspection instruments, and to provide an effective airway which is not readily blocked or obstructed during use.

The present invention is inexpensive to use and easy to insert and therefore appropriate for Emergency Medical Service (EMS) use. This provides advantages over the prior art; the airway devices as shown in the Brain patents can have a tendency for the uninflated collar to pleat or fold during insertion, which results

5

10

15

20

25

30

35

in incomplete expansion of the collar during inflation. Incomplete inflation results in leakage, which prevents effective use of the artificial airway in the manner in which it is intended to be used. Furthermore, the inflatable collars often do not conform well to the airway, also resulting in leakage. In addition, it is often difficult for the individual inserting the artificial airways shown in the Brain patents to determine whether the inflatable collar is completely inflated. In order to overcome these inflation and leakage problems, artificial airways with inflatable collars are often overinflated by the individual inserting the airway to pressures sufficiently high that they can cause damage to the soft tissue against which the inflatable collar seals.

Another difficulty with prior art artificial airways using an inflatable collar, as in the Brain patents, is that it is often difficult for the individual inserting the airway to determine when the airway mask is properly in place over the larynx. uncertainty of proper placement makes complete sealing more difficult, and also complicates insertion of the airway into the patient. Because of this difficulty, the artificial airways of the Brain patents are generally not suitable for EMS use. Additionally, artificial airways with inflatable collars, because they must be completely inflated to properly seal, require a large number of sizes to accommodate the different sizes of airways of the patients to which they are administered. Endotracheal tubes and oro- or naso-pharyngeal airways are also generally not suitable for use by EMS personnel.

Prior art artificial airways can also cause difficulties in ensuring that the artificial airway, or parts of the airway, does not accidentally enter the esophagus during insertion. Entry into the esophagus

5

10

15

20

25

30

35

can cause damage to delicate tissues, which is undesirable and can cause severe complications for the patient. Furthermore, the prior art artificial airways often do not have adequate mechanisms to securely anchor the device in place after insertion, a feature which is important, particularly in EMS use.

The present invention is an artificial airway device used to facilitate lung ventilation in an unconscious patient and methods for using and inserting an artificial airway device, all of which overcome the shortcomings of prior art artificial airway devices. The device of the present invention includes a curved but flexible airway tube and a mask portion, which mask portion includes a mask opening portion and a seating tip. The mask portion is attached to the airway tube at a distal end of the airway tube. The mask opening portion is shaped so as to fit closely adjacent and closely over the patient's laryngeal opening without entering into the larynx and without requiring the mask opening portion to be sealed against the larynx or laryngeal opening. The seating tip includes a series of thin, flexible fins or gills which project from a relatively rigid projecting finger extending axially from, and preferably formed integrally with, the mask opening portion. On one side of the seating tip, at least some of the fins or gills can have an undulating shape across their width, in one embodiment of the invention, to compensate for flexing or expansion of the seating tip as it seats in position. The fins or gills seat against the pharyngeal side of the cricoid, just above the esophagus. In this way, the mask can be properly located above the laryngeal opening, and can be anchored against a relatively hard surface without causing damage to delicate tissue in the esophagus or delicate tissue in or around the larynx or laryngeal opening. The seating tip, and its placement against

mask opening portion is properly in place in the airway, thereby enhancing the ease and accuracy of insertion of the artificial airway in the patient.

5

10

15

20

25

30

35

The artificial airway of the present invention is designed to be easy and convenient to insert in the majority of patients. The artificial airway may also be inexpensively manufactured in quantity, thereby allowing it to be disposable. As a result, the artificial airway of the present invention may be more readily used in EMS or other non-hospital applications, as well as in surgical applications. When the seating tip of the mask portion reaches the pharyngeal side of the cricoid above the esophagus, a definite end-point can be felt by the individual inserting the artificial airway, indicating that the mask portion is correctly placed. The mask portion does not enter the larynx or trachea, and the seating tip does not enter the esophagus, so the risk of damage to these delicate structures is avoided.

Likewise, the risk of accidental entry of the mask portion into the esophagus or one of the main bronchi is also avoided with use of the artificial airway of the present invention. Once in place, the artificial airway is generally used to allow the lungs to be ventilated by positive pressure. Alternatively, the patient may be permitted to breathe spontaneously after insertion of the artificial airway of the present invention.

The seating tip of the present invention may provide some degree of blockage so as to prevent gastric reflux from the stomach and aspiration into the patient's airway, making the artificial airway of the present invention more adaptable to emergency and EMS use, as well as adaptable to a larger variety of surgical applications than prior art artificial airways.

The present invention also includes an inflatable cuff used to anchor the artificial airway in place using the patient's tongue and oro-pharynx behind the uvula. This inflatable cuff is preferably offset relative to the airway tube. The offset of the inflatable cuff helps to ensure that the mask opening portion is held closely near the laryngeal opening, thereby allowing more effective operation of the artificial airway device. The inflatable cuff may be deflated so that the artificial airway device may be more easily inserted into the patient, and thereafter inflated to anchor the artificial airway device in place.

In the method of insertion of an artificial airway according to the present invention, the inflatable cuff is first deflated. The artificial airway is lubricated, and then inserted down the patient's oral cavity. The seating tip of the artificial airway is fed along the hard and soft palate, the back of the oropharynx, and into the cricopharynx adjacent the cricoid. When resistance is felt due to interaction between the seating tip and the cricoid, insertion is halted. The artificial airway is then pulled back slightly, to lift the epiglottis away from the mask opening and so that the inflatable cuff is just behind the uvula. The inflatable cuff is then inflated. The patient may then be ventilated.

BRIEF DESCRIPTION OF THE DRAWINGS

5

10

15

25

30

Other objects and advantages of the invention will be apparent from the specification and claims, when considered in connection with the attached sheets of drawings, illustrating different forms of the invention, wherein like characters represent like parts and in which:

Figure 1 is a perspective view of one embodiment of the artificial airway device of the present invention.

Figure 2 is a side elevation view of the mask portion used with the embodiment of Figure 1.

Figure 3 is perspective view of the embodiment of Figure 2.

Figure 4 is a rear elevation view of a second embodiment of a mask portion which may be used with the embodiment of Figure 1.

Figure 5 is side elevation view of the embodiment of Figure 2.

Figure 6 is a side elevation view of a third embodiment of a mask portion used with airway device of Figure 1.

Fig. 7 is a partially cross-sectional view of the artificial airway device of the present invention, as inserted in the airway of a patient, prior to retraction and inflation.

Fig. 8 is a partially cross-sectional view of the artificial airway device of the present invention, as inserted in the airway of a patient, after retraction and inflation.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

5

10

15

20

25

30

35

Figure 1 is a perspective view of one embodiment of the artificial airway of the present invention. In the embodiment of Fig. 1, a mask portion 100 is connected to a partially curved airway tube 200 which includes a connection end 300. Connection end 300 may be connected to any known device or mechanism for providing artificial or spontaneous ventilation of a patient and/or for providing oxygen, air, anesthesia or other gases to the respiratory system of the patient. An inflation fluid supply unit 400 with a fluid connector 403 is also shown in Figure 1.

In the embodiment shown in Figure 1, the mask portion 100 includes a opening portion 110 and a seating tip 120 extending axially outwardly from the mask opening portion 110. The mask portion 100 is preferably integrally formed in one piece, and includes an opening 101 which securely receives a distal end 201 of the airway tube 200.

The airway tube 200 is assembled into the opening 101 and fixed to the mask portion 100, using any appropriate attachment technique or mechanism. In the preferred embodiment of Fig. 1, the airway tube 200 is made of a material which is sufficiently flexible to permit it to deform so as to fit down the patient's airway (see Figures 7 and 8), but is also sufficiently stiff to permit the airway tube 200 and the mask portion 100 to be accurately positioned manually in the patient P. Polyvinyl chloride (PVC), or any other known inexpensive, durable and partially flexible material may be used as the material from which the airway tube 200 is made.

The airway tube 200 includes a large central bore 204 through which various gases (e.g., anesthesia, oxygen, air) can be administered to the patient, if and when desired. In addition, the airway tube 200

includes a small conduit 202 in the tube wall. In the embodiment shown in Figure 1, the small conduit 202 would be located on the underside (shown on the right in Figure 1) of the airway tube 200. The small conduit 202 is used to transmit a fluid into and out of the interior of the inflatable cuff 800 to inflate and deflate the inflatable cuff 800, and is connected to the fluid supply unit 400.

5

10

15

20

25

30

35

The inflatable cuff 800, which is in the form of a fluid-expandable pillow or cuff, is mounted on the shaft of the airway tube 200, in a location on the tube 200 where it is adjacent the tongue T and behind the uvula U of the patient P in the pharynx when the mask opening portion 110 of the present invention is in place over the larynx L (see Figures 7 and 8). As shown in Figure 1, the inflatable cuff 800 is offset relative to the airway tube 200, such that one side 801. of the inflatable cuff 800 extends a greater distance away from the airway tube 200 than the other side 802. The side 801 which extends a greater distance from the airway tube 200 is preferably located opposite the mask opening 111 of the mask opening portion 110. As a result, and as may be seen in Figure 8, the mask opening portion 110 is located closely adjacent the laryngeal opening over the larynx L of the patient P when the artificial airway of the present invention is in place and the seating tip 120 is seated against the pharyngeal side of the cricoid C. During insertion of the artificial airway of the present invention into the airway of the patient P, the inflatable cuff 800 is in a contracted position (shown in Figure 7). An opening 203 through the wall of airway tube 200 leads from the small conduit 202 to the interior of the inflatable cuff 800. Once the artificial airway of the present invention is in place with the mask opening portion 110 over the laryngeal opening of the larynx L, fluid may

be applied to connector 403, thereby expanding the inflatable cuff 800 to the condition shown in Figure 1. The inflatable cuff 800, in the expanded condition, contacts the tongue T of the patient P and the opposed portion of the oro-pharynx behind the uvula U, thereby anchoring the artificial airway of the present invention in place within the airway of the patient P.

5

10

15

20

25

30

35

The mask portion 100 includes an upper or proximal mask opening portion 110 and a lower or distal seating The mask opening portion 110 includes a mask opening 111 which opens into the distal end 201 of the large conduit 204 in the airway tube 200, thereby allowing gases to be delivered to, and drawn from, the patient's respiratory system. The mask opening portion 110 has a shape 112 surrounding the mask opening 111 which is designed to approximate the shape of the laryngeal opening of the larynx L, thereby covering the laryngeal opening without sealing against the tissues surrounding the laryngeal opening. In this way, the mask opening portion 110 provides virtually complete coverage of the laryngeal opening of the larynx L, helping to prevent the incursion or ingress of anything into the patient's airway other than the gases delivered through the large conduit 204 of the airway tube 200.

The seating tip 120 includes a relatively rigid projecting finger 121 which extends from the mask opening portion 110. Extending radially outwardly from the projecting finger 121 are a series of axially spaced thin and flexible fins or gills 122 and/or 125. Fins or gills 122 and/or 125 are preferably integrally molded with, and made of the same material as, the projecting finger 121. In a preferred embodiment, the entire mask portion 100 could be integrally molded in one piece from a durable biocompatible material such as urethane or polyvinyl chloride (PVC). The fins or

5

10

15

20

25

30

35

gills 122 and/or 125 are designed so that they have a degree of flexibility, and thereby can be compressed or flexed to conform to the area above the esophagus E at the pharyngeal side of the cricoid C. The fins or gills 122 and/or 125 therefore conform and seat against the pharyngeal side of the cricoid C, and the associated area above the esophagus E opposite the pharyngeal side of the cricoid C, thereby anchoring the mask opening portion 110 in the area above the laryngeal opening of the larynx L.

Figures 2 and 3 show details of the mask portion 100 of Figure 1. The mask portion 100 includes an upper or proximal mask opening portion 110 and a lower or distal seating tip 120. The mask opening portion 110 includes an opening 101 which connects with the large conduit 204 in the airway tube 200. A flange 102 may at least partially surround the opening 101 to assist in assembly of the distal end 201 of airway tube 200 to the mask portion 100. The mask opening portion 110 includes a mask opening 111 which connects the large conduit 204 of the distal end 201 of airway tube 200 to the laryngeal opening of the larynx L of the patient P. As shown in Figure 3, the mask opening 111 is formed by a plurality of apertures 142 disposed in and through the surface of the mask opening portion These apertures 142 are used to pass air, oxygen, anesthesia or other gases from the airway tube 200 through the mask portion 100 and into the patient's larynx L. The apertures 142 are separated from one another by a series of bars 143 forming a grate. bars 143 act to restrain any anatomical portion, and in particular the epiglottis G, from entering into and blocking or partially blocking, the mask opening 111, thereby preventing obstruction of the delivery or removal of gases from the respiratory system of the patient P.

5

10

15

20

25

30

35

As shown in particular in Figure 3, the mask opening portion 110 can be formed to have a shape 112 which is approximately trapezoidal, which shape 112 is designed to closely follow the shape of the laryngeal opening of the larynx L above which the mask opening portion 110 is placed. In this manner, the mask opening portion 110 can serve to block the laryngeal opening of the larynx L from the ingress of material or any other object into the larynx L and respiratory system of the patient P, other than the gases which are delivered via the large conduit 204 of the airway tube 200.

In the mask portion of Figures 2 and 3, the seating tip 120 has a shovel-shaped design. As may be seen in Figure 3, the fins or gills 122 and 125 taper in width from the proximal end to the distal end of the projecting finger 121. In addition, at least some of the fins or gills 122 and/or 125 on the side of the mask portion 100 which faces away from the larynx L have a curved shape which extends from one side of two support arms 145 projecting outwardly from the projecting finger 121. As shown in Figure 2, at least some of the fins or gills 122 on the side of the mask portion 100 which faces away from the larynx L may also include undulations 146 across their width. These undulations 146 are used to compensate for flexing or expansion of the seating tip 120 in the direction F as the seating tip is inserted into, and conforms to, the area above the esophagus E where the pharyngeal side of the cricoid C is located and upon which the seating tip 120 seats. On the side of the support arms 145 opposite the fins or gills 122 are fins or gills 125. These fins or gills 125 preferably do not contain undulations, but instead compress as the seating tip flexes or expands in the direction F.

The shovel-shaped, tapered and flexible design of

the embodiment shown in Figures 2 and 3 is preferable in that it can be used in a wide variety of patients, as the shape and flexibility of the seating tip 120 allows it to conform to, and seat in, many different sizes and shapes of patient airways and sizes and shapes of the area above the esophagus at the location of the pharyngeal side of the cricoid C where the seating tip 120 seats.

5

10

15

20

25

30

35

Figures 4 and 5 show an alternative, second embodiment of the mask portion 100' of the present The embodiment of Figures 4 and 5, like the embodiment of Figures 1-3, includes an upper or proximal mask opening portion 110' and a lower or distal seating tip 120'. The mask opening portion 110' includes an opening 101' which connects with the distal end 201 of large conduit 204 in the airway tube 200. flange 102' may at least partially surround the opening 101' to assist in assembly of the airway tube 200 to the mask portion 100'. The mask opening portion 110' includes a mask opening 111' which connects the large conduit 204 of the airway tube 200 to the laryngeal opening of the larynx L of the patient P. As shown in Figure 4, the mask opening 111' is formed by a plurality of apertures 142 disposed in and through the surface of the mask opening portion 110' apertures 142 are used to pass air, oxygen, anesthesia or other gases from the airway tube 200 through the mask portion 100' and into the patient's larynx L. apertures 142 are separated from one another by a series of bars or grates 143. The bars or grates 143 act to restrain any anatomical portion, and in particular the epiglottis G, from entering into and blocking or partially blocking, the mask opening 111', thereby preventing obstruction of the delivery or removal of gases from the respiratory system of the patient P.

As shown in particular in Figure 4, the mask opening portion 110' can be formed to have a shape 112' which is approximately trapezoidal, which shape 112' is designed to closely follow the shape of the laryngeal opening of the larynx L above which the mask opening portion 110' is placed. In this manner, the mask opening portion 110' can serve to block the laryngeal opening of the larynx L from the ingress of material or any other object into the larynx L and respiratory system of the patient P, other than the gases which are delivered via the large conduit of the airway tube 200.

Figure 6 shows an additional embodiment of the mask portion 100", which includes a modified configuration of the fins or gills 122" and projecting finger 121" of the seating tip 120", as well as a slightly different configuration of the shape 112" and the mask opening portion 110". The operation of the embodiment of Figure 6, however, is identical to the embodiments described above.

Figure 7 shows the artificial airway of the present invention in place in a patient P, with the inflatable cuff 800 uninflated, and in place adjacent the tongue T and the portion of the oro-pharynx near the uvula U, but prior to retraction. Figure 8 shows the artificial airway in place in a patient P, after retraction and inflation of the inflatable cuff 800. As shown in Fig. 8, the artificial airway of the present invention, and in particular the mask opening portion 110, seats properly in place above the laryngeal opening L of the patient P. As may also be seen in Figure 8, the seating tip 120 seats in the area above the entrance to the esophagus E against the pharyngeal side of the cricoid C and the portion of the pharynx opposite the pharyngeal side of the cricoid C.

Operation of the various embodiments and methods of their use will now be described, with reference to

5

10

15

20

25

30

35

The patient's P mouth is opened and Figures 7 and 8. the seating tip 120, airway tube 200 and inflatable cuff 800 are lubricated for ease of insertion. artificial airway of the present invention is inserted down the oral cavity 0, with the mask opening 111 facing toward the tongue T during insertion. airway tube 200 is pushed inwardly into the oral cavity O and the seating tip 120 is fed along the hard and soft palate, the back of the oropharynx, and into the cricopharynx adjacent the cricoid C. When resistance is felt due to interaction between the seating tip and the pharyngeal side of the cricoid C above the entrance to the esophagus E, insertion is halted. That position is shown in Figure 7. Once the seating tip 120 seats against the pharyngeal side of the cricoid C, the individual inserting the artificial airway of the present invention will feel the seating tip 120 seating, and therefore will know that the artificial airway of the present invention is properly in place. The airway tube 200 may then be retracted or pulled back slightly outwardly, so that the mask opening portion 110 pushes the epiglottis G up and away from the mask opening 111, as shown in Figure 8. Thereafter, the inflatable cuff 800 is expanded by applying fluid under pressure to connector 403, which fluid travels down the small conduit of the airway tube 200 and enters the interior of inflatable cuff 800 to expand inflatable cuff 800 until it contacts the tongue T and the opposed portion of the oro-pharynx behind the uvula U, thereby securing the artificial airway of the present invention in place. That condition is also shown in Figure 8. Once the artificial airway is in place, any mechanism or structure which is used for the delivery of gases to the respiratory system of the patient may be connected to connection end 300, or the connection end could be left free to allow spontaneous

ventilation by the patient P.

Thus, there is shown and described a unique design and concept of an artificial airway and method of its use and insertion. While this description is directed to particular embodiments, it is understood that those skilled in the art may conceive modifications and/or variations to the specific embodiments shown and described herein. Any such modifications or variations which fall within the purview of this description are intended to be included as part of the invention. It is understood that the description herein is intended to be illustrative only and is not intended to be limitative. Rather, the scope of the invention described herein is limited only by the claims.

15

10

5

CLAIMS

What is Claimed Is:

 An artificial airway, comprising: an airway tube;

a mask opening portion, the mask opening portion including a mask opening connected to the airway tube; and

a seating tip extending axially from the mask opening portion.

- The artificial airway of claim 1, wherein: the seating tip includes a projecting finger.
- 3. The artificial airway of claim 1, wherein: the seating tip includes at least one flexible fin.
- 4. The artificial airway of claim 3, wherein: the seating tip includes a plurality of flexible fins.
- 5. The artificial airway of claim 3, wherein: the at least one flexible fin includes undulations.
- 6. The artificial airway of claim 4, wherein:
 a first plurality of the flexible fins includes
 undulations, and wherein a second plurality of the
 flexible fins do not include undulations.
- 7. The artificial airway of claim 4, wherein:
 the flexible fins taper toward a distal end of the seating tip.

8. The artificial airway of claim 1, wherein: the airway opening is covered by at least one bar.

- 9. The artificial airway of claim 8, wherein: the airway opening is covered by a grate.
- 10. The artificial airway of claim 1, further comprising:

an inflatable cuff, the inflatable cuff being mounted on the airway tube.

- 11. The artificial airway of claim 10, wherein: the inflatable cuff is offset from the airway tube.
- 12. The artificial airway of claim 10, further comprising:

a conduit connected to an interior of the inflatable cuff, the conduit transmitting fluid into and out of the interior of the inflatable cuff.

13. An artificial airway, comprising:
 an airway tube;

a mask opening portion, the mask opening portion including a mask opening connected to the airway tube; and

at least one flexible fin located axially outwardly from the mask opening portion.

14. The artificial airway of claim 13, further comprising:

a plurality of flexible fins.

15. The artificial airway of claim 13, wherein: the at least one flexible fin includes undulations.

23. A method of inserting an artificial airway with a seating tip into a patient, comprising:

opening a mouth of the patient;

inserting the artificial airway into the mouth of the patient; and

inserting the artificial airway into the pharynx of the patient until the seating tip contacts the pharyngeal side of the cricoid.

- 24. The method of claim 23, further comprising: retracting the artificial airway after the seating tip contacts the pharyngeal side of the cricoid.
- 25. The method of claim 24, further comprising:

 pushing the epiglottis up and away from an opening
 on the artificial airway.
- 26. The method of claim 23, further comprising: inflating a cuff on the artificial airway after the seating tip contacts the pharyngeal side of the cricoid.

INTERNATIONAL SEARCH REPORT

International application No. PCT/US00/09702

	SSIFICATION OF SUBJECT MATTER					
	A61M 16/00 207.14					
According to	o International Patent Classification (IPC) or to both	national classification and IPC				
	DS SEARCHED					
	ocumentation searched (classification system followed					
U.S. :	128/898; 200.24, 204.18, 207.14, 207.15-207.17, 207	.19				
Documentat	ion searched other than minimum documentation to the	extent that such documents are included	I in the fields searched			
			·			
	ata base consulted during the international search (na	- of data have and where practicable	search terms used)			
Electronic d	ata base consulted during the international search (na	ine of data base and, where practicable,	scalar terms asso,			
			· · · · · · · · · · · · · · · · · · ·			
c. DOC	UMENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where app	propriate, of the relevant passages	Relevant to claim No.			
X,P	US 5,983,897 A (PAGAN) 16 Novem	ber 1999, entire document.	1-3, 13			
x	US 4,995,388 A (BRAIN) 26 February	1, 3, 10, 12, 13, 20, 22-26				
x	US 5,632,271 A (BRAIN) 27 May 199	97, entire document.	1-3, 13, 23-25			
		•				
	•	•				
	·					
			j			
	La disable and series of Box C	See patent family annex.	1			
Furti	her documents are listed in the continuation of Box C	"T" later document published after the in	remarional filing date or priority			
	occial categories of cited documents: ocument defining the general state of the art which is not considered	date and not in conflict with the appli principle or theory underlying the in-	CEIDOU DAT CITED TO RUGGLERAND INC.			
to	be of particular retevance	-V document of particular relevance; the	ne claimed invention cannot be			
"L" do	urtier document published on or after the international filing date ocument which may throw doubts on priority claim(s) or which is	considered novel or cannot be consid when the document is taken alone	eted to suvoine to macutine such			
ci	ted to establish the publication date of another citation or other secial reason (as specified)	"Y" document of particular relevance; to considered to involve an inventive	e step when the document is			
O do	ocument referring to an oral disclosure, use, exhibition or other means	combined with one or more other su being obvious to a person skilled in	ch documents, such comunistion			
	ocument published prior to the international filing date but later than be priority date claimed	*&* document member of the same pater				
Date of the	actual completion of the international search	Date of mailing of the international se	earch report			
/7 1 9 AUG 2000						
29 JULY	2000	LO AUG 4	nna ,			
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Authorized officer						
Box PCT Washington, D.C. 20231 GLENN K. DAWSON						
Facsimile 1		Telephone No. (703) 308-4304				
Form PCT/I	ISA/210 (second sheet) (July 1998)*					